

855AA
FLEXOR 4SH MSHA
EN 856 4SH



Tube : OIL RESISTANT SYNTHETIC RUBBER
 Reinforcement : FOUR HIGH TENSILE STEEL SPIRALS (4S)
 Cover : ABRASION, OZONE AND HYDROCARBON RESISTANT SYNTHETIC RUBBER
 Application : VERY HIGH PRESSURE HYDRAULIC LINES, FUEL OIL, ANTIFREEZE SOLUTIONS, AIR AND WATER.
 Constant operation : -40°C +100°C
 Ambient temperature : -40°C +80°C
 Fittings : Consult fittings catalogue
 Length : Random up to 1" - 40 m max over 1"
 Branding : ALFAGOMMA FLEXOR 4SH ID... - WP ... MPa (... PSI) - EN 856 4SH DN... - USMSHA IC-152/8 - ... - Q/yr
 Note : S.F.: 4:1

Code	ID mm	ID in	Dash	OD mm	OD in	WP Mpa	WP psi	BP Mpa	BP psi	BR mm	BR in	Weight kg/m	Weight lb/C ft
<u>855AA02000RFB8</u>	19	3/4	-12	32,2	1,27	42	6000	168	24000	280	11,2	1,57	106
<u>855AA02500RFB8</u>	25	1	-16	38,7	1,52	38	5500	152	22000	340	13,6	1,95	131
<u>855AA03200RFB8</u>	32	1.1/4	-20	45,5	1,79	35	5000	140	20000	460	18,4	2,47	165
<u>855AA03800RFB8</u>	38	1.1/2	-24	53,5	2,11	29	4200	116	16800	560	22,4	3,27	219
<u>855AA05100RFB8</u>	51	2	-32	68,1	2,68	25	3650	100	14600	700	28	4,67	313