

898AA
 FLEXOR 12 MSHA
 SAE 100 R12 - EN 856 R12



Tube : OIL RESISTANT SYNTHETIC RUBBER
 Reinforcement : FOUR HIGH TENSILE STEEL SPIRALS (4S)
 Cover : ABRASION, OZONE AND HYDROCARBON RESISTANT SYNTHETIC RUBBER
 Application : VERY HIGH PRESSURE HYDRAULIC LINES, FUEL OIL, ANTIFREEZE SOLUTIONS, AIR AND WATER.
 Constant operation : -40°C +121°C
 Ambient temperature : -40°C +80°C
 Fittings : Consult fittings catalogue
 Length : Random up to 1" - 40 m max over 1"
 Branding : ALFAGOMMA FLEXOR 12 ID... - WP ...MPa (.... PSI) - SAE 100 R12-EN 856 R12 -DN.... -USMSHA.... - Q/yr
 Note : S.F.: 4:1

Code	ID mm	ID in	Dash	OD mm	OD in	WP Mpa	WP psi	BP Mpa	BP psi	BR mm	BR in	Weight kg/m	Weight lb/C ft
<u>898AA01000RTB8</u>	10	3/8	-6	20,3	0,8	28	4000	112	16000	127	5,1	0,61	41
<u>898AA01200RTB8</u>	13	1/2	-8	23,8	0,94	28	4000	112	16000	178	7,1	0,76	51
<u>898AA01600RTB8</u>	16	5/8	-10	27,4	1,08	28	4000	112	16000	203	8,1	1,02	68
<u>898AA02000RTB8</u>	19	3/4	-12	30,7	1,21	28	4000	112	16000	241	9,6	1,19	80
<u>898AA02500RTB8</u>	25	1	-16	38	1,5	28	4000	112	16000	305	12,2	1,76	118
<u>898AA03200RTB8</u>	32	1.1/4	-20	47	1,85	21	3000	84	12000	419	16,8	2,69	180
<u>898AA03800RTB8</u>	38	1.1/2	-24	53,5	2,11	17,5	2500	70	10000	508	20,3	3,08	206
<u>898AA05100RTB8</u>	51	2	-32	66,7	2,63	17,5	2500	70	10000	635	25,4	3,97	266
<u>898AA06300RTB8</u>	64	2.1/2	-40	81,2	3,2	14	2030	56	8120	720	28,8	6,36	426