

845AA
 FLEXOR 2SN - R2AT
 EN 853 2SN - SAE 100 R2AT



Tube : OIL RESISTANT SYNTHETIC RUBBER
 Reinforcement : TWO HIGH TENSILE STEEL BRAIDS (2B)
 Cover : ABRASION, OZONE AND HYDROCARBON RESISTANT SYNTHETIC RUBBER
 Application : HIGH PRESSURE HYDRAULIC LINES, FUEL OIL, ANTIFREEZE SOLUTIONS, AIR AND WATER.
 Constant operation : -40°C +100°C (T max air = +70°C)
 Ambient temperature : -40°C +80°C
 Fittings : Consult fittings catalogue
 Length : Random up to 1" - 40 mt. max over 1"
 Branding : ALFAGOMMA FLEXOR 2AT/2SN ID... - WP ... MPa (... PSI) - SAE 100 R2AT - EN 853 2SN - DN ... - Q/yr
 Note : MSHA cover available: Code 846AA

S.F.: 4:1

Code	ID mm	ID in	Dash	OD mm	OD in	WP Mpa	WP psi	BP Mpa	BP psi	BR mm	BR in	Weight kg/m	Weight lb/C ft
<u>845AA00500HAA8</u>	5	3/16	-3	13,4	0,53	42	6000	168	24000	90	3,6	0,29	19
<u>845AA00600HAA8</u>	6	1/4	-4	15	0,59	40	5800	160	23200	100	4	0,36	24
<u>845AA00800HAA8</u>	8	5/16	-5	16,7	0,66	35	5000	140	20000	115	4,6	0,42	28
<u>845AA01000HAA8</u>	10	3/8	-6	19,1	0,75	33	4800	132	19200	125	5	0,51	34
<u>845AA01200HAA8</u>	13	1/2	-8	22,2	0,87	27,5	4000	110	16000	175	7	0,64	43
<u>845AA01600HAA8</u>	16	5/8	-10	25,4	1	25	3630	100	14520	200	8	0,74	50
<u>845AA02000HAA8</u>	19	3/4	-12	29,3	1,15	21,5	3120	86	12480	240	9,6	0,91	61
<u>845AA02500HAA8</u>	25	1	-16	38,1	1,5	16,5	2400	66	9600	300	12	1,32	88
<u>845AA0324831A8</u>	32	1.1/4	-20	48,3	1,9	12,5	1820	50	7280	420	16,8	1,93	129
<u>845AA0385531A8</u>	38	1.1/2	-24	54,6	2,15	9	1310	36	5240	500	20	2,41	161
<u>845AA0516731A8</u>	51	2	-32	67,4	2,65	8	1160	32	4640	630	25,2	2,96	198
<u>825AA063832RA8</u>	64	2.1/2	-40	83	3,27	7	1000	28	4000	760	30,4	3,96	265
<u>825AA076962RA8</u>	76	3	-48	96	3,78	5,5	800	22	3200	900	36	4,96	332