

T-605 AA  
FUEL-OIL S&D 10 BAR (150 PSI)



TUBE : BLACK CONDUCTIVE NBR  
 REINFORCEMENT : HIGH TENSILE TEXTILE CORDS WITH EMBEDDED STEEL HELIX WIRE  
 COVER : BLACK CR - ABRASION, OZONE AND HYDROCARBON RESISTANT  
 APPLICATION : FUEL AND OIL SUCTION AND DELIVERY. SPECIALLY DESIGNED FOR TANK TRUCK AND GENERAL INDUSTRIAL APPLICATIONS.  
 SAFETY FACTOR : <=127mm 3:1 133-254mm 2.5:1 305mm 1.5:1  
 TEMPERATURE : -30°C +80°C (-22°F +176°F)  
 BRAND TEXT : ALFAGOMMA -ITALY- T-605 10 BAR (150 PSI) PETROLEUM S&D (omega)  
 BRAND TYPE : RED LETTERS  
 APPROVALS :

NOTE :

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	Vac. %	BR mm	Available Length m	Stock Length m
<u>605AA019296MD0</u>	19	3/4	29	5	600	10	150	100	76	20 / 30,5 / 61	30,5 / 61
<u>605AA025356MD0</u>	25	1"	35	5	740	10	150	100	100	20 / 30,5 / 61	30,5 / 61
<u>605AA030406MD0</u>	30	1" 3/16	40	5	840	10	150	100	120	30,5	30,5
<u>605AA032426MD0</u>	32	1" 1/4	42	5	900	10	150	100	128	20 / 30,5 / 61	30,5 / 61
<u>605AA035456MD0</u>	35	1" 3/8	45	5	960	10	150	100	140	30,5	30,5
<u>605AA038486MD0</u>	38	1" 1/2	48	5	1030	10	150	100	152	20 / 30,5 / 61	30,5 / 61
<u>605AA040506MD0</u>	40	1" 9/16	50	5	1070	10	150	100	160	30,5	30,5
<u>605AA042526MD0</u>	42	1" 5/8	52	5	1120	10	150	100	168	30,5	30,5
<u>605AA045556MD0</u>	45	1" 3/4	55	5	1190	10	150	100	180	30,5	30,5
<u>605AA048586MD0</u>	48	1" 7/8	58	5	1260	10	150	100	192	30,5	30,5
<u>605AA051616MD0</u>	51	2	61	5	1330	10	150	100	204	20 / 30,5 / 61	30,5 / 61
<u>605AA057676MD0</u>	57	2" 1/4	67	5	1460	10	150	100	228	20	
<u>605AA060726MD0</u>	60	2" 3/8	72	6	1990	10	150	100	240	30,5	30,5
<u>605AA063756MD0</u>	63	2" 1/2	75	6	2080	10	150	90	252	20 / 30,5	30,5
<u>605AA070826MD0</u>	70	2" 3/4	82	6	2300	10	150	90	280	30,5	30,5
<u>605AA076886MD0</u>	76	3"	88	6	2480	10	150	90	304	20 / 30,5	30,5
<u>605AA080946MD0</u>	80	3" 1/8	94	7	2660	10	150	90	320	30,5	30,5
<u>605AA090046MD0</u>	90	3" 1/2	104	7	3040	10	150	90	360	20 / 30,5	30,5
<u>605AA102166MD0</u>	102	4"	116	7	3400	10	150	90	408	20 / 30,5	30,5
<u>605AA110246MD0</u>	110	4" 5/16	124	7	4160	10	150	90	440	30,5	
<u>605AA115296MD0</u>	115	4" 1/2	129	7	4330	10	150	90	460	30,5	
<u>605AA120386MD0</u>	120	4" 3/4	138	9	5490	10	150	80	480	30,5	
<u>605AA127456MD0</u>	127	5"	145	9	5780	10	150	80	508	30,5	30,5
<u>605AA133516MD0</u>	133	5" 1/4	151	9	6030	10	150	80	532	30,5	30,5
<u>605AA152706MD0</u>	152	6"	170	9	7150	10	150	80	608	30,5	30,5
<u>605AA160786MD0</u>	160	6" 5/16	178	9	7490	10	150	80	640	30,5	30,5
<u>605AA203256MD0</u>	203	8"	225	11	11630	10	150	70	812	6,1	
<u>605AA254766MD0</u>	254	10"	276	11	15670	10	150	70	1016	6,1	
<u>605AA305236MD0</u>	305	12"	327	11	19940	10	150	70	1220	6,1	28/10/2008